



## Carpet Specifications

Fibre:

100% Marine grade SD PP BCF with maximum UV inhibitors added and premium colour stabilization material used for extrusion

Primary Backing:

Marine grade UV stabilized Polypropylene woven cloth with specifically developed adhesives for tuft locking cut and loop pile

Secondary Backing:

Marine grade Polypropylene woven cloth with specifically developed adhesives bonding primary and secondary

Pile Height:

9mm total thickness      7mm fibre pile height plus 2mm secondary backing

Stitch Rate:

8 stitches per inch      675gm/sqm (20oz/sqyd)

Panel Width:

50mm      includes 2x loop lines & 14x cut lines (repeated)

Wear Rating:

Domestic      Heavy Duty  
Commercial      Light Duty

Width:

Teak & Plank      available in 2mtr & 4mtr wide (+/- 1%)  
Plush      available in only 2mtr wide (+/- 1%)

Weight:

2mtr wide carpet      approx. 2.75kgs (6.05lbs) / lineal meter (+/-5%)  
4mtr wide carpet      approx. 5.5kgs (12.10lbs) / lineal meter (+/-5%)

30m Roll Specs:

2mtr wide carpet      2.1mtr Length, 600mm Diameter, 84kgs nominal  
4mtr wide carpet      4.2mtr Length, 600mm Diameter, 167kgs nominal